This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) [In an] <u>An</u> expansion joint cover [having] <u>comprising:</u>

a pair of elongated frames, [each] one of which is adapted to be secured in the lengthwise direction thereof to a building member[, one on] extending along one side of an expansion gap and the other [on] of which is adapted to be secured in the lengthwise direction thereof to another building member extending along the other side of the expansion gap, and each of which frames has [a] an elongated planar support surface extending along the expansion gap, and

(an elongated cover that is adapted to span the expansion gap and is supported on the <u>planar</u> support surfaces of the respective frames for sliding movement of the frames relative to the cover <u>in a direction transverse to the expansion gap</u>,

[the improvement] wherein the cover includes a modular center plate made up of a plurality of formed members, each formed member being rectangular in plan and of uniform cross-section along an axis in the transverse direction thereof and having side edges parallel to the axis, and the formed members being arranged with their side edges adjacent each other and with their ends overlying the planar support surfaces of the frame members for said sliding movement relative thereto.

2. (Original) The improvement according to claim 1, wherein adjacent pairs of formed members are coupled together by joints between the side edges.



- 3. (Original) The improvement according to claim 1, wherein adjacent pairs of formed members are coupled together by slip joints between the side edges.
- 4. (Original) The improvement according to claim 1, wherein all of the formed members of the modular center plate are of the same cross-section.
- 5. (Original) The improvement according to claim 1, wherein the modular center plate includes a continuous edge frame member affixed to each end of the plurality of formed members.

6. (Reinstated) The improvement according to claim 1, wherein each of the formed members is an extrusion and has a continuous planar upper web portion and a plurality of spaced apart dependent ribs extending downwardly from the web portion.

7. (Reinstated) The improvement according to claim 6, wherein each of the ribs is of inverted "T"-shape in cross-section.

- 8. (Original) The improvement according to claim 1, wherein each of the formed members has corrugations.
- 9. (Original) The improvement according to claim 1, wherein each of the formed members has a plurality of transversely spaced-apart planar upper web portions, a plurality of transversely spaced-apart planar lower web portions staggered between the upper web portions, and a rib portion joining each edge of each upper web portion to an edge of each lower web portion.
- 10. (Original) The improvement according to claim 9, wherein the upper web portions of all of the formed members are coplanar and the lower web portions of all of the formed members are coplanar.

yb' con't

(Reinstated) The improvement according to claim 10, wherein the cover further includes a planar sheet supported by and attached to the upper web portions of all of the formed members.

12. (Reinstated) The improvement according to claim 9, wherein the rib portions lie obliquely to the planes of the web portions and define with the lower web portions dovetail-shaped grooves facing upwardly.

13. (Currently amended) [In an] An expansion joint cover [having] comprising:

a pair of elongated frames, [each] <u>one</u> of which is adapted to be secured <u>in the</u>

<u>lengthwise direction thereof</u> to a building member[, one on] <u>extending along</u> one side of an

expansion gap and the other [on] <u>of which is adapted to be secured in the lengthwise direction</u>

<u>thereof to another building member extending along</u> the other side of the expansion gap, and

each of which <u>frames</u> has [a] <u>an elongated</u> planar support surface <u>extending along</u> the expansion

gap, and

an elongated cover that is adapted to span the expansion gap and is supported on the <u>planar</u> support surfaces of the respective frames for sliding movement of the frames relative to the cover <u>in a direction transverse</u> to the expansion gap,

[the improvement] wherein the cover includes a modular center plate that is made up of a plurality of identical formed members, each formed member being rectangular in plan and of uniform cross-section along an axis in the transverse direction thereof and having side edges parallel to the axis and the formed members being arranged with their side edges adjacent each other and with their ends overlying the planar support surfaces of the frames for said sliding

NY02:450350.2 Page 5 of 13

movement relative thereto, and a continuous end frame member affixed to each end of the plurality of formed members.

frame member includes spaced-apart upper and lower flanges forming a groove and the formed members are affixed to the end frame members by reception of end portions thereof in the grooves.

15. (Original) The improvement according to claim 14, wherein each end of the modular center plate is supported on the support surface of the frame member by the lower flange of the end frame member.

16. (Original) The improvement according to claim 13, wherein each end of the modular center plate is supported on the support surface of the frame member by a rod of a rigid low friction polymeric material received in a partially open socket in the end frame member.

(Reinstated) The improvement according to claim 13, wherein each of the formed members is an extrusion and has a continuous planar upper web portion and a plurality of spaced apart dependent ribs extending downwardly from the web portion.

(Reinstated) The improvement according to claim 17, wherein each of the ribs is of inverted "T"-shape in cross-section.

19. (Original) The improvement according to claim 13, wherein each of the formed members is corrugated.

20. (Original) The improvement according to claim 13, wherein each of the formed members has a plurality of transversely spaced-apart planar upper web portions, a plurality of transversely spaced-apart planar lower web portions staggered between the upper

CBI Compt

Serial No. 09/593,785



web portions, and a rib portion joining each edge of each upper web portion to an edge of each lower web portion.